



Bobcat®

PORTABLE POWER

AIR COMPRESSORS

PA185



One Tough Animal™

Model	PA185
COMPRESSOR ROTARY SCREW/ SINGLE STAGE	
Free-Air Delivery*	185(5.24) cfm(m ³ /min)
Unloading Pressure	125(8.6) psig(bar)
Air Discharge Outlet NPT Size	2 x 3/4"
Air Discharge Outlet Quantity	2
Min & Max Limiting Temperatures	-10 °C To 52 °C
Fuel Tank Capacity	32(121) US gal(L)
ENGINE	
Make/Model	Kubota V2403T
Emission Tier Level	Tier II
Number of Cylinders	4
Displacement	148.5(2.4) cu. in(L)
Full Load Speed	2550 (rpm)
Idle Speed	1700 (rpm)
Bhp @ Full Speed	62(46.2) hp(kW)
ENGINE	
Battery	12 (V)
DIMENSIONS WITH RUNNING GEAR	
Length	137.2(3485) in(mm)
Width	68.5(1740) in(mm)
Height	67.5(1715) in(mm)
Track Width	60(1524) in(mm)
Tire Size	ST175/80R13C
Shipping Weight w/o fuel	2094(950) lb(kg)
Working Weight w fuel	2333(1058) lb(kg)

*In Accordance to ISO1217 1996 Annexure E

Product improvement is a continuous goal at Bobcat. Design and specifications are subject to change without notice or obligation

