Phone: +1.323.721.4900
Web: vseaviation.com
Email: sales-montebello@vseaviation.com

VSE Aviation

Parker & Stratoflex

Custom Hose Assemblies

Formerly Desser Aerospace

Teflon Hoses

124 Hose

Meets or exceeds the requirements of MIL-H-27267 (bulk hose), AS1946 and MIL-H-25579



Tube: Extruded, conductive polytetrafluoroethylene. Electrical conductivity conforms to MIL-DTL-25579
Reinforcement:
Sizes -3 thru -12: one corrosion resistant steel wire braid
Sizes -16Z thru -24Z: one corrosion resistant steel wire braid

124J Hose

Meets or exceeds the requirements of MIL-H-27267 (bulk hose), and MIL-H-25579. Similar to AS1723



Tube: Extruded, conductive polytetrafluoroethylene. Electrical conductivity conforms to MIL-DTL-25579
Reinforcement:
Sizes -3 thru -12: one corrosion resistant steel wire braid
Sizes -16Z thru -24Z: one corrosion resistant steel wire braid
Cover: Integral fire resistant silicone

124K Hose

Meets or exceeds the requirements of MIL-H-27267 (bulk hose), AS1946 and MIL-H-25579



Tube: Extruded, conductive polytetrafluoroethylene. Electrical conductivity conforms to MIL-DTL-25579
Reinforcement:
Sizes -3 thru -12: one corrosion resistant steel wire braid
Sizes -16Z thru -24Z: two corrosion resistant steel wire braids

171 Hose

Meets or exceeds the requirements of MIL-H-27267 (bulk hose), AS1946 and MIL-H-25579



Tube: Extruded, conductive polytetrafluoroethylene.
Electrical conductivity conforms to MIL-DTL-25579
Reinforcement: High density braid of small diameter corrosion resistant steel wire

© VSE Aviation - 08052026

Rubber Hoses

101 Hose

Meets or exceeds AS4897 requirements

Tube: Seamless, extruded, conductive aerospace polytetrafluoroethylene
Reinforcement: Corrosion-resistant steel wire braid
Cover: Integral silicone



193 Hose (5593)

Meets or exceeds MIL-H-5503 requirements

Tube: Seamless Buna-N
Reinforcement: One braid of hair tensile fiber cord
Cover: Synthetic rubber



111 Hose (8794)

Meets MIL-H-8794, MIL-H-8795 and MIL-A-5070 requirements

Tube: Seamless synthetic rubber
Reinforcement: One fiber braid and one high tensile steel wire braid
Cover: Fiber braid impregnated with oil and mildew resistant rubber



130 Hose

Meets or exceeds MIL-H-87974 requirements

Tube: Seamless synthetic rubber
Reinforcement: One fiber braid and one high tensile steel wire braid
Cover: Synthetic rubber-impregnated, oil resistant fiber braid. The cover is black in color



156 Hose

Meets the dimensional requirements and meets or exceeds the functional requirements of MIL-H83797

Tube: Seamless HSP elastomer
Reinforcement: One and one-half corrosion resistant steel wire braids



© VSE Aviation - 08052026